

CS11-747 Neural Networks for NLP

Learning From/For Knowledge Bases

Graham Neubig



Carnegie Mellon University

Language Technologies Institute

Site

<https://phontron.com/class/nn4nlp2019/>


Knowledge Bases

- Structured databases of knowledge usually containing
 - Entities (nodes in a graph)
 - Relations (edges between nodes)
- How can we **learn to create/expand knowledge bases** with neural networks?
- How can we **learn from the information in knowledge bases** to improve neural representations?
- How can we use structured knowledge to answer questions (see also semantic parsing class)

Types of Knowledge Bases

WordNet (Miller 1995)


- WordNet is a large database of words including parts of speech, semantic relations



- Nouns: is-a relation (hatch-back/car), part-of (wheel/car), type/instance distinction
- Verb relations: ordered by specificity (communicate -> talk -> whisper)
- Adjective relations: antonymy (wet/dry)

Cyc (Lenant 1995)

- A manually curated database attempting to encode all common sense knowledge, 30 years in the making



DBPedia (Auer et al. 2007)

- Extraction of structured data from Wikipedia

Carnegie Mellon University

From Wikipedia, the free encyclopedia

Carnegie Mellon University (**Carnegie Mellon** or **CMU** /kɑːrnɛɡi ˈmɛlon/ or /kɑːrneɪɡi ˈmɛlon/) is a private research university in Pittsburgh, Pennsylvania.

Founded in 1900 by Andrew Carnegie as the Carnegie Technical Schools, the university became the Carnegie Institute of Technology in 1912 and began granting four-year degrees. In 1967, the Carnegie Institute of Technology merged with the Mellon Institute of Industrial Research to form Carnegie Mellon University.

The university's 140-acre (57 ha) main campus is 3 miles (5 km) from Downtown Pittsburgh. Carnegie Mellon has seven colleges and independent schools: the College of Engineering, College of Fine Arts, Dietrich College of Humanities and Social Sciences, Mellon College of Science, Tepper School of Business, H. John Heinz III College of Information Systems and Public Policy, and the School of Computer Science. The university also has campuses in Qatar and Silicon Valley, with degree-granting programs in six continents.

Carnegie Mellon is ranked 25th in the United States and 77th in the world by *U.S. News & World Report*.^[9] It is home to the world's first degree-granting Robotics and Drama programs,^[10] as well as one of the first Computer Science departments.^[11] The university was ranked 89th for R&D in 2016 having spent \$242 million.^[12]

Carnegie Mellon counts 13,650 students from 114 countries, over 100,000 living alumni, and over 5,000 faculty and staff. Past and present faculty and alumni include 20 Nobel Prize Laureates,^[13] 12 Turing Award winners, 22 Members of the American Academy of Arts & Sciences,^[14] 19 Fellows of the American Association for the Advancement of Science, 72 Members of the National Academies, 114 Emmy Award winners, 44 Tony Award laureates, and 7 Academy Award winners.^[15]

Structured data

Coordinates: 40°44′33.22″N 79°04′35.63″W﻿ / ﻿40.7428111°N 79.0765639°W﻿ / 40.7428111; -79.0765639

Carnegie Mellon University



Former names	Carnegie Technical Schools (1900–1912) Carnegie Institute of Technology (1912–1967) Carnegie-Mellon University (1968–1988) ^[1] Carnegie Mellon University (1988–present)
Motto	"My heart is in the work" (Andrew Carnegie)
Type	Private university
Established	1900 by Andrew Carnegie

- owl:Thing
- dul:Agent
- dul:SocialPerson
- wikidata:Q24229398
- wikidata:Q3918
- wikidata:Q43229
- dbpedia:Agent
- dbo:EducationalInstitution
- rdfs:Organisation
- dbo:University
- geo:SpatialThing
- schema:CollegeOrUniversity
- schema:EducationalOrganization
- schema:Organization
- umbel-rc:Business
- umbel-rc:EducationalOrganization
- umbel-rc:Organization
- umbel-rc:University


Freebase/WikiData

(Bollacker et al. 2008)

- *Curated* database of entities, linked, and extremely large scale

Richard Feynman ▼

[Discuss "Richard Feynman"](#) [Hide Empty Fields](#)



◀ image 1 of 1 ▶

Types: [Person \(People\)](#), [Author \(Publishing\)](#), [Physicist \(Science\)](#), [Deceased Person \(People\)](#), [Film writer \(Film\)](#), [influence Node \(mikelove's types\)](#), [Person Or Being In Fiction \(Fictional Universes\)](#), [Book Subject \(Publishing\)](#)

Also known as: [Richard Phillips Feynman](#)

Gender: [Male](#)

Date of Birth: [May 11, 1918](#)

Place of Birth: [Far Rockaway, Queens](#)

Country Of Nationality: [United States](#)

Profession: [Physicist](#), [Scientist](#)

Religion: [Atheism](#)

Parents: [double-click to add](#)

Children: [Michelle Louise Feynman](#), [Carl Feynman](#)

Siblings:

- [Joan Feynman](#) Person
- [Richard Feynman](#) ..(Richard Phillips Feynman, Author, Physicist, Deceased Person, Film)
- [Ana Gasteyer](#) Person, Film actor, TV Actor, Theater Actor
- [Gervase of Tilbury](#) Person
- [Alec Baldwin](#) ..(Alexander Rae Baldwin, Person, Film actor, Film director, Film producer, TV)
- [Ernest Thesiger](#) Person, Film actor, Deceased Person
- [Mean Girls](#) Film
- [Riverside Drive](#) Landscape project
- [Ferrat et Jennie](#) Film
- [Television Personalities](#) (The Television Personalities)

[Create New Person](#)

Page History
Created by Metaweb Oct 22, 2006
Last edited by robert Oct 20, 2007

Web Link(s)
[double-click to add](#)

Employment history
[Cornell University](#)
[California Institute of Technology](#)
[Thinking Machines](#)

Education
[Princeton University](#) • 1942 • Ph.D.
[Massachusetts Institute of Technology](#) • 1939 • Bachelor's degree

Quotations
[Joan Feynman](#) Person
Joan Feynman (b. 31 March 1928) is an astrophysicist who made original studies of the interactions between the solar wind and the Earth's magnetosphere. While working at the NASA Ames Research Centre in 1971, Feynman showed that coronal mass ejections could be identified by the presence of helium in...

Books Written
[What Do You Care What Other People Think?](#)
[The Pleasure of Finding Things Out](#)
[The Feynman Lectures on Physics](#)
[Surely You're Joking, Mr. Feynman!](#)


Learning Representations for Knowledge Bases

Learning Knowledge Graph Embeddings (Bordes et al. 2013)

- Motivation: express triples as additive transformation
- Method: minimize the distance of existing triples with a margin-based loss that

$$\sum_{(h,\ell,t) \in \mathcal{S}} \sum_{(h',\ell,t') \in \mathcal{S}'_{(h,\ell,t)}} [\gamma + d(\mathbf{h} + \ell, \mathbf{t}) - d(\mathbf{h}' + \ell, \mathbf{t}')]_+$$

- Note: one vector for each relation, additive modification only, intentionally simpler than NTN



(a) TransE


Decomposable Relation

Model (Xie et al. 2017)

- Idea: There are many relations, but each can be represented by a limited number of “concepts”
- Method: Treat each relation map as a mixture of concepts, with sparse mixture vector α

$$f_r(h, t) = \|\alpha_r^H \cdot \mathbf{D} \cdot \mathbf{h} + \mathbf{r} - \alpha_r^T \cdot \mathbf{D} \cdot \mathbf{t}\|_\ell$$


- Better results, and also somewhat interpretable relations



Multi-hop Relational Context w/ Graph Neural Networks (Schlichtkrull et al., 2017)

- Idea: consider all the local neighborhood entities instead of each triples
- Method: apply the message-passing framework using Graph Convolutional Network

$$h_i^{(l+1)} = \sigma \left(\sum_{r \in \mathcal{R}} \sum_{j \in \mathcal{N}_i^r} \frac{1}{c_{i,r}} W_r^{(l)} h_j^{(l)} + W_0^{(l)} h_i^{(l)} \right)$$





- Recurrent application will allow capturing K-hop neighbor nodes.

Knowledge Base Incompleteness

- Even w/ extremely large scale, knowledge bases are by nature incomplete
- e.g. in FreeBase 71% of humans were missing “date of birth” (West et al. 2014)
- Can we perform “relation extraction” to extract information for knowledge bases?

Remember: Consistency in Embeddings

e.g. king-man+woman = queen (Mikolov et al. 2013)



Relation Extraction w/ Neural Tensor Networks (Socher et al. 2013)

- A first attempt at predicting relations: a multi-layer perceptron that predicts whether a relation exists

$$u_R^T f(W_{R,1}e_1 + W_{R,2}e_2)$$

- Neural Tensor Network: Adds bi-linear feature extractors, equivalent to projections in space

$$g(e_1, R, e_2) = u_R^T f\left(e_1^T W_R^{[1:k]} e_2 + V_R \begin{bmatrix} e_1 \\ e_2 \end{bmatrix} + b_R\right)$$

- Powerful model, but perhaps overparameterized!

Learning from Text Directly

Distant Supervision for Relation Extraction (Mintz et al. 2009)

- Given an entity-relation-entity triple, extract all text that matches this and use it to train

[Steven Spielberg]'s film [Saving Private Ryan] is loosely based on the brothers' story.

Allison co-produced the Academy Award-winning [Saving Private Ryan], directed by [Steven Spielberg]...

- Creates a large corpus of (noisily) labeled text to train a system

Relation Classification w/ CNNs (Zeng et al. 2014)

- Extract features w/o syntax using CNN
 - Lexical features of the words themselves
 - Features of the whole span extracted using convolution




Figure 1: Architecture of the neural network used for relation classification.





Figure 2: The framework used for extracting sentence level features.

Jointly Modeling KB Relations and Text (Toutanova et al. 2015)

- To model textual links between words w/ neural net: aggregate over multiple instances of links in dependency tree


Textual Pattern	Count
SUBJECT $\xrightarrow{\text{appos}}$ founder $\xrightarrow{\text{prep}}$ of $\xrightarrow{\text{pobj}}$ OBJECT	12
SUBJECT $\xleftarrow{\text{nsubj}}$ co-founded $\xrightarrow{\text{dobj}}$ OBJECT	3
SUBJECT $\xrightarrow{\text{appos}}$ co-founder $\xrightarrow{\text{prep}}$ of $\xrightarrow{\text{pobj}}$ OBJECT	3
SUBJECT $\xrightarrow{\text{conj}}$ co-founder $\xrightarrow{\text{prep}}$ of $\xrightarrow{\text{pobj}}$ OBJECT	3

- Model relations w/ CNN



Modeling Distant Supervision Noise in Neural Models (Luo et al. 2017)

- Idea: there is noise in distant supervision labels, so we want to model it



- By controlling the “transition matrix”, we can adjust to the amount of noise expected in the data
 - Trace normalization to try to make matrix close to identity
 - Start training w/ no transition matrix on data expected to be clean, then phase in on full data

Using Knowledge Bases to Inform Neural Models

Retrofitting of Embeddings to Existing Lexicons (Faruqui et al. 2015)


- Similar to joint learning, but done through post-hoc transformation of embeddings
 - Advantage of being usable with any pre-trained embeddings
- Double objective of making transformed embeddings close to neighbors, and close to original embedding

$$\Psi(Q) = \sum_{i=1}^n \left[\alpha_i \|q_i - \hat{q}_i\|^2 + \sum_{(i,j) \in E} \beta_{ij} \|q_i - q_j\|^2 \right]$$

- Can also force antonyms away from each-other (Mrksic et al. 2016)

Injecting Knowledge into Language Models (Hayashi et al. 2020)


- Provide LMs with topical knowledge in the form of copiable graphs
 - Each (Wiki) text is given relevant KB taken from Wikidata
- Examine all possible decoding "paths" and maximize the marginal probability



Reasoning over Text Corpus as a Knowledge Base (Dhingra et al. 2020)

- Answering questions using text corpora as a traceable KB
- Relevance matching over **mentions**

1. Create mention vectors
2. Retrieve relevant mentions from pre-trained models
3. Aggregate scores



Schema-Free Extraction

Open Information Extraction

(Banko et al 2007)

- Basic idea: **the text is the relation**
- e.g. "United has a hub in Chicago, which is the headquarters of United Continental Holdings"
 - {United; has a hub in; Chicago}
 - {Chicago; is the headquarters of; United Continental Holdings}
- Can extract any variety of relations, but does not abstract

Rule-based Open IE

- e.g. TextRunner (Banko et al. 2007), ReVerb (Fader et al. 2011)
- Use parser to extract according to rules
 - e.g. relation must contain a predicate, subject object must be noun phrases, etc.
- Train a fast model to extract over large amounts of data
- Aggregate multiple pieces of evidence (heuristically) to find common, and therefore potentially reliable, extractions

Neural Models for Open IE

- Unfortunately, heuristics are still not perfect
- Possible to create relatively large datasets by asking simple questions (He et al. 2015):

UCD **finished** the 2006 championship as Dublin champions ,
by **beating** St Vincents in the final .

finished

Who finished something? - UCD
What did someone finish? - the 2006 championship
What did someone finish something as? - Dublin champions
How did someone finish something? - by beating St Vincents in the final

beating

Who beat someone? - UCD
When did someone beat someone? - in the final
Who did someone beat? - St Vincents

- Can be converted into OpenIE extractions, for use in supervised neural BIO tagger (Stanovsky et al. 2018)

Learning Relations from Relations


Modeling Word Embeddings vs. Modeling Relations

- Word embeddings give information of the word in context, which is indicative of KB traits
- However, other relations (or combinations thereof) are also indicative
 - This is a *link prediction* problem in graphs

Tensor Decomposition

(Sutskever et al. 2009)


- Can model relations by decomposing a tensor containing entity/relation/entity tuples



Matrix Factorization to Reconcile Schema-based and Open IE Extractions

(Riedel et al. 2013)

- What to do when we have a knowledge base, and text from OpenIE extractions?
- **Universal schema:** embed relations from multiple schema in the same space



Modeling Relation Paths

(Lao and Cohen 2010)


- Multi-step paths can be informative for indicating individual relations
- e.g. “given word, recommend venue in which to publish the paper”

ID Weight Feature

1	26.9	$word \xrightarrow{HasTitle^{-1}} paper \xrightarrow{In} journal$
2	4.5	$word \xrightarrow{HasTitle^{-1}} paper \xrightarrow{FirstAuthor} author \xrightarrow{FirstAuthor^{-1}} paper \xrightarrow{In} journal$
3	2.8	$word \xrightarrow{HasTitle^{-1}} paper \xrightarrow{AnyAuthor} author \xrightarrow{AnyAuthor^{-1}} paper \xrightarrow{In} journal$
4	1.1	$gene \xrightarrow{GeneticallyRelated} gene \xrightarrow{HasGene^{-1}} paper \xrightarrow{In} journal$
5	0.9	$gene \xrightarrow{HasGene^{-1}} paper \xrightarrow{In} journal$
6	0.6	$e^* \xrightarrow{AnyPaper} paper \xrightarrow{Cite} paper \xrightarrow{In} journal$

Optimizing Relation Embeddings over Paths (Guu et al. 2015)


- Traveling over relations might result in error propagation
- Simple idea: optimize so that after traveling along a path, we still get the correct entity



Differentiable Logic Rules

(Yang et al. 2017)

- Consider whole paths in a differentiable framework



- Treat path as a sequence of matrix multiplies, where the rule weight is a

$$\sum_l \alpha_l \prod_{k \in \beta_l} \mathbf{M}_{R_k}$$

Questions?